

SPOT GEN4

GLOBAL SATELLITE GPS MESSENGER

SPOT devices deliver affordable, reliable, location-based tracking, messaging and life-saving S.O.S. technology to hundreds of thousands of users around the world 24/7.

ENHANCED TRACKING SERVICES

CUSTOM TRACKING RATE

SPOT Gen4's customized tracking allows you to change the rate tracks are sent to 2 ½, 5, 10, 30, or 60 minutes. Extreme Tracking upgrade is required for 2 ½ minute tracking.

MOTION-ACTIVATED TRACKING

A vibration sensor tells SPOT to send your GPS location when you are moving and to stop when you do. This conserves battery power and avoids sending duplicate tracks.

CONTINUOUS TRACKING

SPOT Gen4 will send track messages until you turn off your SPOT. No need to reset after 24 hours.



POTENTIAL APPLICATIONS

HELP/SPOT ASSIST

Request help from your colleagues at your GPS location or ask for help from professional assistance organizations.

TRACK

Automatically send and save your location and allow contacts to track your progress using SPOT My Globalstar.

CHECK IN

Let contacts know where you are and that you're okay with a pre-programmed message.

CUSTOM MESSAGE

Let contacts know where you are by sending a pre-programmed message with your GPS location.

S.O.S.

In an emergency, send an S.O.S. with your GPS location to GEOS, who facilitates search and rescue.

BATTERY TYPE

- 4 AAA Energizer® Ultimate Lithium 8x batteries (L92)
- 4 AAA Energizer® NiMH rechargeable batteries (NH12)

LONG BATTERY LIFE

Send 1,250 Check In and Custom Messages on a single set of Lithium batteries

SPECIFICATIONS

HEIGHT: 3.48" (8.83 cm) **WIDTH:** 2.66" (6.76 cm)

THICKNESS: 0.93" (2.36 cm)

WEIGHT: 5 oz (142 g) with Lithium batteries

OPERATING TEMP: -22 F to 140 F (-30 C to 60 C)

OPERATING ALTITUDE: -328 ft to +21,320 ft (-100 m to +6,500 m)

HUMIDITY RATED: MIL-STD 810F, Temperature cycling from 20°C to 60°C while maintaining 95% RH.

VIBRATION RATED: Per SAE J1455

DUST AND WATER RESISTANT: IP68